

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

Amendments to the Claims

Please amend the claims as follows:

1. (Currently amended): A method of determining a ~~transit delay~~ total processing overhead delay between a first node and a second node in a ~~hierarchical~~ network connected to both the first node and the second node, the method comprising:

a) determining interim transit delays processing overhead delays between adjacent nodes in a communications path between the start node and the end node including the following steps:

- ea1) sending a first signal from a common node to the first node;
- ba2) receiving a first response signal at the common node from the first node in response to the first signal;
- ea3) determining a first round trip time, the first round trip time being a time elapsed between steps a) and b);
- da4) sending a second signal from the common node to the second node;
- ea5) receiving a second response signal at the common node from the second node in response to the second signal;
- fa6) determining a second round trip time, the second round trip time being a time elapsed between steps d) and e); and
- ga7) calculating the transit delay between the first node and the second node according to the formula

$$D(X,Y)= | R(NMC,X)-R(NMC,Y) | /2$$

where

D(X,Y) is the transit delay between first node X and second node Y;

R(NMC,X) is the first round trip time;

R(NMC,Y) is the second round trip time; and

NMC is the common node;

a8) subtracting a previously determined minimum transit delay between the first node and the second node with the transit delay between the first node and the second node; and

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

b) calculating the total transit overhead processing delay between the start node and the end node by adding up the interim transit processing overhead delays.

2. (Original): A method as in claim 1 wherein at least one of the first and second nodes are directly connected to the common node.

3. (Original): A method as in claim 1 wherein at least one of the first and second nodes are indirectly connected to the common node.

4. (Original): A method as in claim 1 wherein the common node is a network management computer.

5. (Original): A method as in claim 1 wherein the hierarchical network is a portion of a mesh network.

6. (Cancelled):

7. (Cancelled):

8. (Cancelled):

9. (Cancelled):

10. (Cancelled):

11. (Cancelled):

12. (Cancelled):

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

13. (Original): A method of determining the quality of communications between two nodes in a network, the method comprising:

- a) measuring a transit delay between the two nodes at different times resulting in a plurality of transit delay measurements;
- b) calculating a jitter among the plurality of time delay measurements; and
- c) determining if the jitter exceeds a predetermined threshold value.

14. (Original): A method as in claim 13 wherein the network is a hierarchical network and the transit delay is measured between a first node and a second node using the following method:

- a) sending a first signal from a common node to the first node;
- b) receiving a first response signal at the common node from the first node in response to the first signal;
- c) determining a first round trip time, the first round trip time being a time elapsed between steps a) and b);
- d) sending a second signal from the common node to the second node in response to the second signal;
- e) receiving a second response signal at the common node from the second node in response to the second signal;
- f) determining a second round trip time, the second round trip time being a time elapsed between steps d) and e); and
- g) calculating the transit delay between the first node and the second node according to the formula

$$D(X,Y)=|R(NMC,X)-R(NMC,Y)|/2$$

where

$D(X,Y)$ is the transit delay between first node X and second node Y;

$R(NMC,X)$ is the first round trip time;

$R(NMC,Y)$ is the second round trip time; and

NMC is the common node.

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

15. (Original): A method as in claim 13 wherein the transit delay is measured between a start node and an end node in a hierarchical network using the following method:

a) determining interim transit delays between adjacent nodes in a communications path between the start node and the end node; and

b) calculating the total transit delay between the start node and the end node by adding up the interim transit delays.

16. (Original): A method as in claim 14 wherein the hierarchical network is a portion of a mesh network.

17. (Original): A method as in claim 15 wherein the hierarchical network is a portion of a mesh network.

18. (Original): A method as in claim 13 wherein step c) includes determining if at least one of the transit delay measurements exceeds a predetermined threshold value.

19. (Original): A method of determining a jitter between two transit delay measurements between two nodes, the method comprising:

calculating the jitter based on

$$J(A,D,t) = D(A,D,t2) - D(A,D,t1))$$

where

J(A,D,t) is the jitter between the two transit delay measurements;

D(A,D,t1) is one of the two transit delay measurements taken at time t1;

D(A,D,t2) is the other of the two transit delay measurements taken at time t2; and

A and D are the two nodes between which the transit delay is measured.

20. (Original): A method as in claim 19 wherein the two nodes are directly connected to each other.

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

21. (Original): A method as in claim 19 wherein the two nodes are indirectly connected to each other.

22. (Currently amended): A method of determining a total jitter between a start node and an end node in a network, the method comprising:

- a) determining interim jitters in transit delays between adjacent nodes ~~in~~ based on a communications path between the start node and the end node;
- b) calculating the total jitter ~~in~~ based on transit delays between the start node and the end node by adding up the interim jitters.

23. (Original): A method of determining a jitter between a plurality of transit delay measurements between two nodes, the method comprising :

calculating the jitter based on

$$J(A, B) = \frac{\sqrt{\sum_{i=1}^M D(A, B, i)^2}}{\sum_{i=1}^M D(A, B, i)}$$

where

$J(A, B)$ is the jitter between the plurality of transit delay measurements;

$D(A, B, i)$ is the i th transit delay measurement among the plurality of transit delay measurements; and

M is the number of transit delay measurements.

24. (Original): A method as in claim 23 wherein the two nodes are directly connected to each other.

25. (Original): A method as in claim 23 wherein the two nodes are indirectly connected to each other.

Application No. 09/599,963

November 9, 2004

Reply to office action of August 9, 2004

26. (Original): A method of determining a signal processing time in a node, the method comprising:

- a) determining at least one round trip delay time of a transmission between a node A and a node K;
- b) determining a round trip delay time of a transmission between a node B and a node K;
- c) determining a lowest recorded value for the round trip delay time between node A and node K;
- d) calculating the signal processing time through node A according to:

$$P(A) = R(K,B) - \text{minimum}(R(K,A))$$

where

P(A) is the signal processing time through node A;

R(K,B) is a round trip delay time between node B and node K; and

(minimum (R(K,A))) is the lowest recorded value for the round trip delay time between node A and node K.